

7.6.1

O-Ringe NBR, FPM Passend zu Progress Metall Kabelverschraubungen metrisch

O-rings NBR, FPM suitable for metallic Progress cable glands metric versions

AGRO No	M	iD mm	d mm	
O-Ring: NBR		O-ring: NBR		
Einsatztemperatur: -20°/+100°C		Temp. range: -20°/+100°C		
1005.00.08	M 6	5,0	1,0	1
1006.00.08	M 8	6,0	1,5	1
1006.06.08	M10	8,1	1,6	1
1007.00.08	M12	10,0	1,5	1
1000.09.00.08	M16	13,1	1,6	1
2111.00.08	M20	17,0	2,0	1
1013.00.22.08	M25	22,0	2,0	1
1021.00.30.08	M32	30,0	2,0	1
1000.40.00.08	M40	37,8	2,6	1
1000.50.00.08	M50	46,0	2,0	1
1000.63.00.08	M63	60,0	2,0	1
1000.75.00.08	M75	72,0	2,0	1




O-Ring: FPM
Einsatztemperatur: -25°/+200°C

O-ring: FPM
Temp. range: -25°/+200°C

1105.98.08	M 6	5,0	1,0	1
1106.98.08	M 8	6,0	1,5	1
1106.06.98.08	M10	8,1	1,6	1
1107.98.08	M12	10,0	1,5	1
1100.09.98.08	M16	13,1	1,6	1
2111.98.08	M20	17,0	2,0	1
1113.98.22.08	M25	22,0	2,0	1
1121.98.30.08	M32	30,0	2,0	1
1100.40.98.08	M40	37,8	2,6	1
1100.50.98.08	M50	46,0	2,0	1
1100.63.98.08	M63	60,0	2,0	1
1100.75.98.08	M75	72,0	2,0	1

Technische Änderungen vorbehalten!



Technical modifications are subject to change!



7.6.2

O-Ringe NBR, FPM Passend zu Progress Metall Kabelverschraubungen Pg

O-rings NBR, FPM suitable for metallic Progress cable glands Pg versions

AGRO No	 Pg	iD mm	d mm	
O-Ring: NBR		O-ring: NBR		
Einsatztemperatur: -20°/+100°C		Temp. range: -20°/+100°C		
1007.00.08	Pg 7	10,0	1,5	1
1000.09.00.08	Pg 9	13,1	1,6	1
1011.00.08	Pg 11	15,0	2,0	1
1016.00.08	Pg 13	19,0	2,0	1
1016.00.08	Pg 16	19,0	2,0	1
1016.00.25.08	Pg 21	25,0	2,0	1
1029.00.08	Pg 29	33,0	2,2	1
1036.00.08	Pg 36	42,5	2,6	1
1000.42.00.08	Pg 42	48,0	3,0	1
1000.48.00.08	Pg 48	55,0	2,0	1




O-Ring: FPM
Einsatztemperatur: -25°/+200°C

O-ring: FPM
Temp. range: -25°/+200°C

1107.98.08	Pg 7	10,0	1,5	1
1100.09.98.08	Pg 9	13,1	1,6	1
1111.98.08	Pg 11	15,0	2,0	1
1116.98.08	Pg 13	18,0	2,0	1
1116.98.08	Pg 16	18,0	2,0	1
1116.98.25.08	Pg 21	25,0	2,0	1
1129.98.08	Pg 29	33,0	1,8	1
1136.98.08	Pg 36	42,5	2,6	1
1100.42.98.08	Pg 42	48,0	3,0	1
1100.48.98.08	Pg 48	55,0	2,0	1

Technische Änderungen vorbehalten!

Technical modifications are subject to change!



7.6.3

Dichtungsscheiben

Sealing washers

Material: Klinger SIL 4300
 Farbe: grün
 Einsatztemp.: Von -30°/+ 300°C

Material: Klinger SIL 4300
 Colour: green
 Temp. range: -30°/+ 300°C

AGRO No	M/Pg	D1 mm	D2 mm	mm	
Dichtungsscheiben zu Anschlussgewinde metrisch		Sealing washers suitable for entry thread metric			
1006.00.16	M 6	10,0	6,0	1,5	1
1008.00.16	M 8	12,0	8,0	1,5	1
1010.00.16	M10	14,0	10,0	1,5	1
1012.00.16	M12	16,0	12,0	1,5	1
1017.00.16	M16	21,0	16,0	1,5	1
1020.00.16	M20	25,0	20,0	1,5	1
1025.00.16	M25	31,0	25,0	2,0	1
1032.00.16	M32	39,0	32,0	2,0	1
1040.00.16	M40	48,0	40,0	2,0	1
1050.00.16	M50	59,0	50,0	2,0	1
1063.00.16	M63	73,0	63,0	2,0	1



Dichtungsscheiben zu Anschlussgewinde Pg

Sealing washers suitable for entry thread Pg

1007.00.16	Pg 7	16,5	12,5	1,5	1
1009.00.16	Pg 9	19,0	15,2	1,5	1
1011.00.16	Pg 11	22,5	18,5	1,5	1
1013.00.16	Pg 13	25,0	20,5	1,5	1
1016.00.16	Pg 16	27,0	22,5	1,5	1
1021.00.16	Pg 21	33,5	28,5	2,0	1
1029.00.16	Pg 29	43,5	37,0	2,0	1
1036.00.16	Pg 36	55,0	47,0	2,0	1
1042.00.16	Pg 42	63,0	54,0	2,0	1
1048.00.16	Pg 48	69,0	59,3	2,0	1

Technische Änderungen vorbehalten!

Technical modifications are subject to change!