

# AX61400

## 4U 14-slot Rackmount Chassis



### Features

- ▶ Three 5.25" and max. two 3.5" disk drive bays
- ▶ One 12cm ball-bearing fan (optional two hot-swappable fans)
- ▶ Supports 14-slot backplane or ATX MB
- ▶ Single PS/2 size power supply supported



Top view

Default 1 x 12cm fan  
Optional 2 x 8cm hot-swap fan (AX61400H)



### Specifications

Standard Color	T-Black color; W-Beige color (PANTONE 414C)	Expansions	14-slot backplane
Construction	Heavy-duty cold-rolled steel	Speaker	One 0.4W speaker
Drive Capacity	Exposed 3 x 5.25" and 1 x 3.5" drives; internal 1 x 3.5" drive	Operating Temperature Range	0°C (32°F) to 40°C (104°F)
Cooling	one 12cm ball-bearing fan (78CFM) with a removable filter (Optional two 8cm hot-swap fans)	Dimensions (W x D x H)	19" (482.6mm) x 17.7" (450mm) x 7" (177mm)
Front Panel Indicators	1 x power on/off; 1 x HDD		
Front Panel Controls	1 x power on/off; 1 x system reset		
Front Panel Connectors	2 x USB; 1 x PS2 mini-DIN keyboard		
Pre-punched Panel	1 x 25-pin; 1 x DIN 5-pin keyboard		
Hold-down Clamp	height adjustable clamps with rubber cushions		
System Board	SBCs or 12" x 9.6" ATX MB		

## Power Supply Options

Items	Specifications		
	Input	Output	MTBF
ATX 300W (PFC)	AC 100/240V (Auto)	+5V @ 20A +12V @ 14A +3.3V @ 14A -12V @ 0.8A +5VSB @ 2A	100,000 hours
ATX 400W (PFC)	AC 100/240V (Auto)	+5V @ 30A +12V @ 15A -12V @ 0.8A +3.3V @ 30A +5VSB @ 2A	100,000 hours
ATX 500W (PFC)	AC 100/240V (Auto)	+5V @ 30A +12V @ 17A -3.3V @ 30A +5VSB @ 2A	100,000 hours

## Backplane Options

Models	Slots per Segment (ISA/PCI/CPU)	Segment
ATX6022/13L	8/4/1	Single
ATX6020/14	13/0/1	Single
ATX6022/14	9/4/1	Single
ATX6022/14G	1/12/1	Single
ATX6022/14D	2/4/1	Dual

## Ordering Information

AX61400T(W)B/X400	4U rackmount chassis, 14-slot version, 1x12cm fan, with ATX 400W power supply
AX61400T(W)B/X300	4U rackmount chassis, 14-slot version, 1x12cm fan, with ATX 300W power supply
AX61400T(W)M/X400	4U rackmount chassis, MB version, 1x12cm fan, with ATX 400W power supply
AX61400T(W)M/X300	4U rackmount chassis, MB version, 1x12cm fan, with ATX 300W power supply
AX61400HT(W)B/X400	4U rackmount chassis, 14-slot version, 2x8cm hot-swap fan, with ATX 400W power supply
AX61400HT(W)B/X300	4U rackmount chassis, 14-slot version, 2x8cm hot-swap fan, with ATX 300W power supply
AX61400HT(W)M/X400	4U rackmount chassis, MB version, 2x8cm hot-swap fan, with ATX 400W power supply
AX61400HT(W)M/X300	4U rackmount chassis, MB version, 2x8cm hot-swap fan, with ATX 300W power supply

\* T-Black color; W-Beige color

## Optional Items

ATX 300W	power supply with PFC
ATX 400W	power supply with PFC
ATX 500W	power supply with PFC
14-slot to MB version	interchangeable kit
MB to 14-slot	interchangeable kit

\*T-Black color; W-Beige color

## Dimensions

